



GMWL628IXALUS 60CM 4 BURNER GAS COOKTOP



FEATURES & BENEFITS



IXLIUM

Whirlpool introduces an innovative material aimed at all those who love design, but hate cleaning. Thanks to an exclusive nano-technology treatment, the iXelium cooktop is extremely easy to clean. Unlike a standard steel top, iXelium prevents food residuals from sticking to the surface so all you need to do to remove dirt is a soft sponge and non aggressive detergent. The result is a cooking surface which will remain shiny over time without scratches.



BOOSTER

Enjoy super fast boiling times with the Booster cooking zone.



POWERFUL BURNER

Enjoy tastier results, faster. Seal your meat to perfection, boil water faster or enjoy a perfect stir-fry dishes with the outstanding Power Burner 3.500W.



CAST IRON TRIVETS & WOK SUPPORT

Traditional Cast Iron for a premium finish, durability and long lasting quality features, including Wok Support.



SPEED TO BOIL

Enjoy faster boiling. Our innovative technology, by effectively harnessing the energy of the flames, ensures more heat is delivered directly to your pots and pans allowing you to enjoy ideal cooking results, sooner.



MULTILEVEL FLAME

9 flame levels for different cooking methods. Always get the ideal flame for your cooking methods, to achieve perfect cooking results effortlessly.



WARRANTY

Guarantees peace of mind and value for money knowing that any product fault or defect is covered by full replacement parts and/or a service call to ensure the product works as described.

TECHNICAL SPECIFICATIONS

MAIN COLOUR FINISH	Stainless Steel Ixelium
PRODUCT DIMENSIONS	W 590mm x H 41mm x D 510mm
CUT OUT DIMENSIONS	W 560mm x H 38mm x D 480mm
BURNERS	4, Black
CONTROLS	4 Front Knobs
TRIVETS	2 Cast Iron
IGNITION	Electric
SAFETY	Flame Failure
ELECTRICAL RATING	
ELECTRICAL CONNECTION	Plug and Supplied
INSTALLATION	Built-In
NET WEIGHT	
ACCESSORIES INCLUDED	LPG Jets Included, Cast Iron Trivets and wok support
WARRANTY	5 years

BURNER SPECIFICATIONS

AUXILIARY	
NPG: Pressure, Injector & Rate	1.00kPa, 0.85mm & 3.60Mj/h
ULPG: Pressure, Injector & Rate	2.75kPa, 0.52mm & 3.60Mj/h
SEMI-RAPID	
NPG: Pressure, Injector & Rate	1.00kPa, 1.10mm & 5.9Mj/h
ULPG: Pressure, Injector & Rate	2.75kPa, 0.67mm & 5.9Mj/h
SEMI-RAPID	
NPG: Pressure, Injector & Rate	1.00kPa, 1.10mm & 5.9Mj/h
ULPG: Pressure, Injector & Rate	2.75kPa, 0.67mm & 5.9Mj/h
DUAL RING	
NPG: Pressure, Injector & Rate	1.00kPa, 1.65mm & 12.6Mj/h
ULPG: Pressure, Injector & Rate	2.75kPa, 0.95mm & 12.6Mj/h